

DERWENT-ACC-NO: 1995-243376  
DERWENT-WEEK: 199532  
COPYRIGHT 1999 DERWENT INFORMATION LTD

TITLE: Paper tray type container mfg method - by bending  
over side walls  
longitudinally and adhering them to part of sidewalls cuff  
part, so that use of  
thick paper is avoided

PATENT-ASSIGNEE: IIJIMA T[IIJII], TAMA HANKIN KK[TAMAN]

PRIORITY-DATA: 1993JP-0315910 (November 22, 1993)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE
PAGES	MAIN-IPC	
JP 07149341 A	June 13, 1995	N/A
005	B65D 005/24	

APPLICATION-DATA:

PUB-NO	APPL-DESCRIPTOR	APPL-NO
APPL-DATE		
JP07149341A	N/A	1993JP-0315910
November 22, 1993		

INT-CL\_(IPC): B65D005/24

ABSTRACTED-PUB-NO: JP07149341A

BASIC-ABSTRACT: The method entails the formation of the  
recess and the  
projection part to form the section which is in the form of  
a continuous  
alternating sine wave. A wick stencil paper is used as a  
linear sheet stuck to  
one side of a planar-shaped substance of each recess and  
projection part.

Two side-walls (13a-13d) are articulated on each edge of a  
bottom wall (12).

The side-walls (14a,14b) are bent over longitudinally and  
adhered to the cuff  
side-wall. The tongue sides (15a-15d) are articulated and  
adhered to the edge  
of the side-walls.

58/113

ADVANTAGE - Mfr of inexpensive container made of paper for  
e.g. food, with high  
strength, simple mfg process and thick paper material does  
not have to be used.

CHOSEN-DRAWING: Dwg.1/4

TITLE-TERMS:

PAPER TRAY TYPE CONTAINER MANUFACTURE METHOD BEND SIDE WALL  
LONGITUDE ADHERE  
PART SIDEWALL CUFF PART SO THICK PAPER AVOID

DERWENT-CLASS: Q32